



109 Independence Way
 Coatesville, PA 19320
 P: 610-857-2655
 F: 610-857-2986
 graphics@uticom.net
 www.uticom.net

Part # U3550D-AFH-R
 U7000 Material

© Uticom Systems Inc. 2014
 Proprietary and confidential information contained in this drawing is property of Uticom Systems Inc. and is only intended to be viewed by the end user or authorized distributor. Any reproduction in part or as a whole is strictly prohibited unless approved in writing by Uticom Systems, Inc.

Please review this drawing for accuracy. Approved by: _____ Date: _____

White on red background

5"

▲USI U3550D-AFH-R

DANGER

Arc Flash and Shock Hazard.
Appropriate PPE Required.

Do not operate controls or open covers without appropriate personal protection equipment.
Failure to comply may result in injury or death!

Refer to NFPA 70E for minimum PPE requirements.

3.5"

1/4" Rcorners x4

All other graphics print black on white background

U7000 Material: 0.007" retro-reflective sheeting, road sign grade with enclosed optical lens elements, engineering grade. Printed using automotive grade solvent based ink, thickness dry .0004" +/- .0001" with 30 micron emulsion, applied using a 158 mesh screen. Short term UV cured inks are not acceptable. **Over laminate:** 0.002" UV filtering PVDF over laminate. **Adhesive:** 0.0015" solvent based, permanent acrylic ASTM grade D 4956 Class 1 with .007" protective liner, kraft coated one side, with back slit. After 72 hours non removable intact. Water based adhesives or film liners are not acceptable in any part of this construction.

Durability: Minimum lifetime exterior durability of 20-25 years with proper surface preparation. Defective materials will be replaced at no charge.